



Hollow Rubber Stoppers

E4-AB112	1"
E4-1678004	1-1/8"
E4-AB114	1-1/4"
E4-1678008	1-3/8"
E4-AB115	1-1/2"
E4-1678012	1-5/8"
E4-AB116	1-3/4"
E4-AB117	2"
E4-857	1-1/2" x 1-3/4"
E4-1678002	1"



E2-B254-B
Titeseal Tank Ball



E4-8051
Rubber Suction
Stopper Universal Fit

WLCS-1000
Chemical/Lead



Part Number	Model Number	Reduces	Rating (nominal)	Operating Pressure	Operating Temperature
F1-155584-51	W-250	99% of Dissolved Lead, 99.5% of Giardia & Cryptosporidium Cysts, Mercury, Asbestos, Chlorine taste & Odor, Sediment	0.5 micron	30-100 PSI	40-100°F

FloPlus
WFPA



Part Number	Model Number	Sump Color	Cap Color	Intel/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Maximum Flow Rate
F1-152091	WFP3/8-10	Gray	Black	3/8"	4-1/2" x 12"	30-100 PSI	40-100°F	5 gpm
F1-152090	WFP3/4C-10	Gray	Black	3/4"	5-1/8" x 12-1/4"	30-100 PSI	40-100°F	15 gpm
F1-152089	WFP3/4-10	Gray	Black	3/4"	5-1/8" x 12-1/2"	30-100 PSI	40-100°F	15 gpm
F1-152088	WFP1-108B	Gray	Black	1"	7-1/4" x 13-1/8"	30-100 PSI	40-100°F	15 gpm
F1-152087	WFP1.5-208B	Gray	Black	1-1/2"	7-1/4" x 23-3/8"	30-100 PSI	40-100°F	15 gpm

WWHC
Multi-Stage



Part Number	Model Number	Reduces	I/O	Overall Dimensions	Rating (Nominal)	Operating Pressure	Operating Temperature
F1-152022	WWHC	Bad Taste & Odor and Chlorine Taste & Odor	1" NPT	15-1/4" x 7-1/2" x 26-1/2"	25 micron	30-90 PSI	40-100°F
Replacement Cartridge Set							
F1-155333-51	WWHR	Bad Taste & Odor and Chlorine Taste & Odor	-	-	25 micron	30-90 PSI	40-100°F

Filter
Housing
Sline Line



Part Number	Model Number	Sump Color	Cap Color	Intel/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature
F1-152001	W385-PR	Gray	Black	3/8" NPT	4-1/2" x 7"	30-125 PSI	40-100°F
F1-152002	W38-PRA	Gray	Black	3/8" NPT	4-1/2" x 7"	30-125 PSI	40-100°F

Filter Standard



Part Number	Model Number	Sump Color	Cap Color	Intel/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature
F1-152047	W34-PR	Gray	Black	3/4" NPT	5-1/8" x 12 1/4"	30-125 PSI	40-100°F
F1-152018	W34-PR	Clear	Black	3/4" NPT	5-1/8" x 12 1/4"	30-125 PSI	40-100°F
F1-152003	WVC34	Clear	Black	3/4" NPT	5-1/8" x 12 1/4"	30-125 PSI	40-100°F

Filter Housing Heavy-Duty



Part Number	Model Number	Sump Color	Cap Color	Intel/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature
F1-152014	W10-PR	Gray	Black	1"	7-1/4" x 13 1/8"	30-100 PSI	40-100°F
F1-152015	W210-PR	Gray	Black	1"	7-1/4" x 23 3/8"	30-100 PSI	40-100°F
F1-152016	W15-PR	Gray	Black	1-1/2"	7-1/4" x 13 5/8"	30-100 PSI	40-100°F
F1-152017	W2015-PR	Gray	Black	1-1/2"	7-1/4" x 23 2/8"	30-100 PSI	40-100°F
F1-152080	W10-BC	Clear	Blue	1"	7-1/4" x 13 1/8"	30-100 PSI	40-100°F

Spun Polypropylene



Part Number	Model Number	Medium	Rating (Nominal)	Maximum Flow Rate	Diameter	Length
F1-155014-52	W5P	Polypropylene	5 micron	10 gpm	2-3/8"	9-7/8"
F1-155015-52	W25P	Polypropylene	25 micron	10 gpm	2-3/8"	9-7/8"

Pleated Cellulose



Part Number	Model Number	Medium	Rating (Nominal)	Maximum Flow Rate	Diameter	Length
F1-155001-52	W20CLA	Cellulose	20 micron	12 gpm	2 5/8"	9 3/4"
Heavy-Duty-Cartridges						
F1-155405-51	W20CLHD	Cellulose	20 micron	20 gpm	4 1/2"	9 3/4"
F1-155305-51	W20CLHD20	Cellulose	20 micron	20 gpm	4 1/2"	20"

Pleated Polyester



Part Number	Model Number	Medium	Rating (Nominal)	Maximum Flow Rate	Diameter	Length
F1-155038-52	W3OPE	Polyester	30 micron	12 gpm	2-5/8"	9-3/4"

Polypropylene Stringwound



Part Number	Model Number	Medium	Rating (Nominal)	Maximum Flow Rate	Diameter	Length
F1-155186-52	W5W	Polypropylene	5 micron	7 gpm	2-3/8"	9-7/8"
F1-155187-52	W30W	Polypropylene	30 micron	10 gpm	2-3/8"	9-7/8"
F1-155214-52	W50W	Polypropylene	50 micron	10 gpm	2-3/8"	9-7/8"

Carbon Block



Part Number	Model Number	Medium	Reduces	Rating (Nominal)	Chlorine T & O Reduction @ Flow Rate	Lead	Vocs	Diameter	Length
F1-155169-51	W.5CB478	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts	0.5 micron	3000 gal @ 1 gpm	N/A	N/A	2-7/8"	4-7/8"
F1-155162-51	W.5CB	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts	0.5 micron	20000 gal @ 1 gpm	N/A	N/A	2-7/8"	9-3/4"
F1-155170-51	W.5CBHD	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts	0.5 micron	5000 gal @ 4 gpm	N/A	N/A	4-5/8"	9-3/4"
F1-155268-51	WLC-R	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts Lead VOCs	0.5 micron	20000 gal @ 0.6 gpm	600	300	2-7/8"	9-3/4"

Carbo-Impregnated Cellulose



Part Number	Model Number	Medium	Chlorine T&O Reduction @ Flow Rate	Maximum Flow Rate	Diameter	Length
F1-155022-52	W5CIP478	Carbon Impregnated Cellulose	5 micron	10 gpm	2-3/8"	9-7/8"
F1-155002-52	W5CIP	Carbon Impregnated Cellulose	25 micron	10 gpm	2-3/8"	9-7/8"

Radial-Flow Carbon



Part Number	Model Number	Medium	Chlorine T&O Reduction @ Flow Rate	Maximum Flow Rate	Diameter	Length
F1-155141-51	WRC25HD	Granular Activated Carbon	50000 gal @ 3 gpm	3 gpm	4-1/2"	9-2/4"
F1-155247-51	WRC25HD20	Granular Activated Carbon	100000 gal @ 4 gpm	8 gpm	4-1/2"	20"

Quick-Connect In-Line



Part Number	Model Number	Medium	Chlorine T&O Reduction @ Flow Rate	Operating Pressure	Temperature Range	Diameter	Length
F1-155070-51	WICA	Granular Activated Coconut Carbon	1950 gal @ 0.5 gpm (6-month filter life)	20-125 psi	40-100°F	2"	6"

Standard Housing Bracket Kit



Part Number	Model Number	Description
Buna-N		
F1-152040	WMB38	For slim line housings, 3/8" Intel/outlet. Constructed Of zinc- plated steel.

Part Number	Model Number	Description
Buna-N		
F1-152030	W34-OR	For 3/4" Intel/Outlet Housings
F1-152031	W38-OR	For 3/8" Slim Line Housings
F1-152032	W10-OR	For 1" and 1 1/2" Slim Line Housings
F1-151231-51	OR-233	For Wlcs-1000, Wro-3000 And Wro-3500 Filtration Systems
F1-151254	WBC-OR	For 1" and 1 1/2" Heavy-Duty Clear Housings (Square-Cut O-ring)
F1-152033	WG34G	Gasket For W34 & Wc34 (Both Models Obsolete)
Silicone		
F1-151118	W34-ORS	For 3/4" Intel/Outlet High-temperature Housings

O - Rings
FDA-Grade

